Representative Image

Catalog No. 1SVR405601R8000

Description: CR-P110DC2 Pluggable interface relay 2c/o, A1-A2=110VDC, 250V/8A

UPC No 4013614498305

Home > Controls & Protective Relays > Interface Relays & Optocouplers

Descriptors

Category	Interface Relays & Optocouplers

Specifications

Function	Pluggable pcb interface relay CR-P
Rated Control Supply Voltage	110 V DC
Output Signal	250 V / 8 A
Output	2 c/o (SPDT) contacts
Contact material	silver-nickel alloy (AgNi)
Product Main Type	CR-P
Sub-Function	Relay w/o built in LED
RoHS Status	Following EU Directive 2011/65/EU
Object Classification Code	K

Classifications

ETIM 4	EC001437 - Switching relay
ETIM 5.0	EC001437 - Switching relay
ETIM 6.0	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	7.0 27371601

Dimensions

Product Net Width	12.7 mm
Product Net Height	15.7 mm
Product Net Depth / Length	29 mm
Product Net Weight	0.014kg

Package Information

Package Level 1 Units	10 piece
Package Level 1 Width	332 mm

Package Information

Package Level 1 Height	28 mm
Package Level 1 Depth / Length	17 mm
Package Level 1 Gross Weight	0.157 kg
Package Level 1 EAN	4013614373046

Ordering

Minimum Order Quantity	10
Customs Tariff Number	85364900
ECCN	N
ECN	N
ABB MDF Code	3DL - Relays (LV / Control + Protection)
ABB Business Unit	ELSP - Smart Power