

S802-LINK125



Products → Low Voltage Products and Systems → Modular DIN Rail Products
→ High Performance Circuit Breakers HPCBs Accessories

General Information

Extended Product Type:	S802-LINK125
Product ID:	2CCS800900R0562
EAN:	7612271419103
Catalog Description:	S802-LINK125 Pole connector
Long Description:	The pole connector S802-LINK125 can be used up to 125 A. It was developed for photovoltaics and can be used up to 1200V DC.

Ordering

EAN:	7612271419103
Minimum Order Quantity:	2 piece
Customs Tariff Number:	85389030

Dimensions

Product Net Width:	53.7 mm
Product Net Height:	49.5 mm
Product Net Length:	53 mm
Product Net Depth:	69.7 mm
Product Net Weight:	149 g

Container Information

Package Level 1 Units:	2 piece
Package Level 1 Width:	105 mm
Package Level 1 Height:	99 mm
Package Level 1 Length:	60 mm
Package Level 1 Gross Weight:	170 g
Package Level 1 EAN:	7612271419103

Environmental

Ambient Air Temperature:	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Degree of Protection:	acc. to IEC 60529 IP20
Product Main Type:	S802-LINK

Product Name:	Pole connector
Rated Frequency (f):	50 / 60 Hz
Rated Insulation Voltage (U_i):	1200 V DC
Rated Operational Current (I_e):	125 A
Recommended Screw Driver:	Pozidriv 2
RoHS Date:	20170426
Standards:	IEC 60439-2
Terminal Type:	Screw Terminals
Tightening Torque:	3.5 N·m

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	2CCC413003C0203
Declaration of Conformity - CE:	2CCC413029M0401
Environmental Information:	2CCY413207D0202
Instructions and Manuals:	2CCC413029M0402
RoHS Information:	2CCC413008D0206

Classifications

ETIM 4:	EC001522 - Busbar
ETIM 5:	EC001522 - Busbar
ETIM 6:	EC001522 - Busbar
Object Classification Code:	F

