



Malleable Iron Conduit Bushings with Copper Lug

The threaded insulated conduit bushings are superior to common zinc die cast bushings in tensile strength by as much as 25%. They are not subject to temperature/stress creep which can lessen the useful life of the bushing.

Features

- Plastic liner will not chip, crack, swell or shrink
- Resists corrosion, chemicals and temperature extremes
- Eliminates the use of the locknut

Standard Materials

- Malleable Iron

Standard Finish

- Zinc Plated

Applicable Third Party Standards

- CULUS 514B, 467, File Number: E212551
- NEMA FB-1
- Patent #: US 6,808,181



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Box	Case	Weight Per C (lb)
BRC-50-1CKON	½	1.06	0.69	100	500	10
BRC-50S-1CKON	½	1.06	0.69	100	500	10
BRC-75-1CKON	¾	1.25	0.69	50	250	13
BRC-75S-1CKON	¾	1.25	0.69	50	250	13
BRC-100-1CKON	1	1.63	0.75	50	250	18
BRC-100S-1CKON	1	1.63	0.75	50	250	18
BRC-125S-1CKON	1¼	2.00	0.81	25	125	21
BRC-125-1CKON	1¼	2.00	0.81	25	125	21
BRC-125-2CKON	1¼	2.00	0.81	25	125	32
BRC-125S-2CKON	1¼	2.00	0.81	25	125	32
BRC-150-2CKON	1½	2.31	0.81	25	125	37
BRC-150S-1CKON	1½	2.31	0.81	25	125	25
BRC-150-1CKON	1½	2.31	0.81	25	125	25
BRC-150S-2CKON	1½	2.31	0.81	25	125	37
BRC-200S-1CKON	2	2.75	0.88	10	50	30
BRC-200-2CKON	2	2.75	0.88	10	50	41
BRC-200S-2CKON	2	2.75	0.88	10	50	41
BRC-200-1CKON	2	2.75	0.88	10	50	30



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Box	Case	Weight Per C (lb)
BRC-250-3CKON	2½	3.31	1.00	10		91
BRC-250-4CKON	2½	3.31	1.00	10		101
BRC-250-2CKON	2½	3.31	1.00	10		67
BRC-250S-4CKON	2½	3.31	1.00	10		101
BRC-250S-3CKON	2½	3.31	1.00	10		91
BRC-250S-2CKON	2½	3.31	1.00	10		67
BRC-300S-4CKON	3	4.00	1.00	10		116
BRC-300-3CKON	3	4.00	1.00	10		106
BRC-300S-2CKON	3	4.00	1.00	10		82
BRC-300-4CKON	3	4.00	1.00	10		116
BRC-300-2CKON	3	4.00	1.00	10		82
BRC-300S-3CKON	3	4.00	1.00	10		106
BRC-350S-4CKON	3½	4.38	1.06	10		122
BRC-350S-3CKON	3½	4.38	1.06	10		112
BRC-350-3CKON	3½	4.38	1.06	10		112
BRC-350-4CKON	3½	4.38	1.06	10		121
BRC-400S-3CKON	4	5.06	1.13	10		143
BRC-400S-4CKON	4	5.06	1.13	10		153
BRC-400-3CKON	4	5.06	1.13	10		143
BRC-400-4CKON	4	5.06	1.13	10		153
BRC-500S-4CKON	5	6.06	1.19	5		197
BRC-500S-3CKON	5	6.06	1.19	5		187
BRC-500-4CKON	5	6.13	1.19	5		197
BRC-500-3CKON	5	6.13	1.19	5		187
BRC-600-3CKON	6	7.19	1.19	5		224
BRC-600-4CKON	6	7.19	1.19	5		234
BRC-600S-4CKON	6	7.19	1.19	5		234
BRC-600S-3CKON	6	7.19	1.19	5		224