



Malleable Iron Conduit Bushings with Aluminum Lug

The threaded insulated conduit bushings are superior to common zinc die cast bushings in tensile strength by as much as 25%. They are not subject to temperature/stress creep which can lessen the useful life of the bushing.

Features

- Plastic liner will not chip, crack, swell or shrink
- Resists corrosion, chemicals and temperature extremes
- Eliminates the use of the locknut

Standard Materials

- Malleable Iron

Standard Finish

- Zinc Plated

Applicable Third Party Standards

- CULUS 514B, 467, File Number: E212551
- NEMA FB-1
- Patent #: US 6,808,181



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Box	Case	Weight Per C (lb)
BRC-50S-1AKON	1/2	1.06	0.69	100	500	7
BRC-50-1AKON	1/2	1.06	0.69	100	500	7
BRC-75S-1AKON	3/4	1.25	0.69	50	250	11
BRC-75-1AKON	3/4	1.25	0.69	50	250	11
BRC-100S-1AKON	1	1.63	0.75	50	250	15
BRC-100-1AKON	1	1.63	0.75	50	250	15
BRC-125-1AKON	1 1/4	2.00	0.81	25	125	18
BRC-125S-2AKON	1 1/4	2.00	0.81	25	125	23
BRC-125S-1AKON	1 1/4	2.00	0.81	25	125	18
BRC-125-2AKON	1 1/4	2.00	0.81	25	125	23
BRC-150S-2AKON	1 1/2	2.31	0.81	25	125	28
BRC-150-1AKON	1 1/2	2.31	0.81	25	125	23
BRC-150-2AKON	1 1/2	2.31	0.81	25	125	28
BRC-150S-1AKON	1 1/2	2.31	0.81	25	125	23
BRC-200S-1AKON	2	2.75	0.88	10	50	27
BRC-200-1AKON	2	2.75	0.88	10	50	27
BRC-200-2AKON	2	2.75	0.88	10	50	32
BRC-200S-2AKON	2	2.75	0.88	10	50	32



Catalog Number	Trade Size	Dim A (in)	Dim B (in)	Box	Case	Weight Per C (lb)
BRC-250-2AKON	2½	3.31	1.00	10		57
BRC-250S-4AKON	2½	3.31	1.00	10		70
BRC-250S-3AKON	2½	3.31	1.00	10		67
BRC-250S-2AKON	2½	3.31	1.00	10		57
BRC-250-3AKON	2½	3.31	1.00	10		67
BRC-250-4AKON	2½	3.31	1.00	10		70
BRC-300-2AKON	3	4.00	1.00	10		73
BRC-300-3AKON	3	4.00	1.00	10		83
BRC-300S-3AKON	3	4.00	1.00	10		83
BRC-300S-2AKON	3	4.00	1.00	10		73
BRC-300-4AKON	3	4.00	1.00	10		85
BRC-300S-4AKON	3	4.00	1.00	10		85
BRC-350S-3AKON	3½	4.38	1.06	10		88
BRC-350-4AKON	3½	4.38	1.06	10		90
BRC-350-3AKON	3½	4.38	1.06	10		88
BRC-350S-4AKON	3½	4.38	1.06	10		90
BRC-400-4AKON	4	5.06	1.13	10		121
BRC-400-3AKON	4	5.06	1.13	10		119
BRC-400S-3AKON	4	5.06	1.13	10		119
BRC-400S-4AKON	4	5.06	1.13	10		121
BRC-500-3AKON	5	6.13	1.19	5		163
BRC-500-4AKON	5	6.13	1.19	5		165
BRC-500S-3AKON	5	6.13	1.19	5		163
BRC-500S-4AKON	5	6.13	1.19	5		165
BRC-600S-4AKON	6	7.19	1.19	5		203
BRC-600-4AKON	6	7.19	1.19	5		203
BRC-600S-3AKON	6	7.19	1.19	5		201
BRC-600-3AKON	6	7.19	1.19	5		201