

Product data sheet

Specifications



APC Smart-UPS Ultra On-Line,
2200VA, Lithium-ion, Rack/Tower
1U, 120V, 5x 5-20R, 1x L5-20R
NEMA outlets, Network Card,
Extended runtime, W/rail kit

SRTL2K2RM1UNC

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V 125 V
Product or Component Type	Uninterruptible power supply (UPS)
Other Input Voltage	120 V 125 V
Main Output Voltage	120 V
Other Output Voltage	120 V 125 V
Kw Rating	1950 W
rated power in VA	2200 VA
Input Connection Type	NEMA 5-20P
output connection type	5 NEMA 5-20R 1 NEMA L5-20R
Number of rack unit	1U
Cable length	8 ft (2.4 m)
Number of cables	1
Battery Type	Li-Ion (Lithium Ion)
Provided equipment	RJ45 Cable USB cable Country-specific detachable power cord Rack Mounting brackets Rack Mounting support rails Installation guide Warranty card
Range of Product	Smart-UPS Ultra

Batteries & Runtime

Run Time	View Runtime Graph
Typical recharge time	1.5 h
RBC Quantity	1
Battery Voltage	50 V
Battery Charge Power (Watts)	448 W

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Extendable Run Time	1
Replacement battery	APCRBC173-Li 

General

Redundant	No
-----------	----

Physical

color	Silver grey
Height	1.7 in (43 mm)
Width	17.008 in (432 mm)
Depth	22.05 in (560 mm)
Product Weight	35.05 lb(US) (15.9 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit Tower-mounted with kit
Two post mountable	1
USB compatible	Yes

Input

Input Frequency	50/60 Hz
-----------------	----------

Output

Max Configurable Power (Watts)	1950 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
Topology	On-Line
Waveform Type	Sine wave
Bypass type	Internal Bypass (Automatic and Manual)
Maximum configurable power in VA	2200 VA

Conformance

Product Certifications	UL/cUL listed FCC
Standards	UL 1778 CSA C22.2 No.107.3-05 FCC Part 15 class A

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0...15240 m)

Acoustic level	55 dB
IP degree of protection	IP20

Communications & Management

Pre-Installed SmartSlot™ Cards	Network management card with environmental monitoring
control panel	Multi-function LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use

Ordering and shipping details

GTIN	731304435563
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.94 in (27.8 cm)
Package 1 Width	22.20 in (56.4 cm)
Package 1 Length	30.08 in (76.4 cm)
Package 1 Weight	53.31 lb(US) (24.18 kg)

Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	5818
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	8c493f2b-82c6-495f-a54a-f7d594e2b537
REACH Regulation	REACH Declaration

Use Again

Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions



Offer Marketing Illustration

Product benefits / Features

Input Connection Plug Type
NEMA 5-20P



Image of product / Alternate images

Alternative







