

EMO Series

- Maintenance-free nickel-cadmium battery (RC version nickel-metal hydride)
- Injection-molded, high-impact, UV-stabilized, UL94 V-0 thermoplastic construction
- Universal J-box pattern knock-out & mounting plate w/ quick connect features
- Fully adjustable glare free LED heads
- RC version provides 3.44 watts for 90 minutes

Oval 2 Headed Emergency Light



9"Wx4.75"Hx2.75"D

ORDERING INFORMATION

CATALOG #	DESCRIPTION	FINISH	VOLTS
EMO2A	Oval 2 headed emergency light	White	120/277
EMO2ARC	Oval 2 headed emergency light - Remote Capable	White	120/277

ERD Series

- Long-life, efficient ultra-bright white LED
- Mirror-bright reflector and prismatic polycarbonate refractor
- Die-cast aluminum housing
- Durable powder-coated finish
- Sealed and gasketed
- Cold-weather unit for use in temperatures as low as -30°C

Architectural Emergency Light



6.125"Wx10.5"Hx3.625"D

ORDERING INFORMATION

CATALOG #	DESCRIPTION	FINISH	VOLTS
ERD12BZ	Architectural LED Emergency Light with Photocell	Bronze	120/277
ERD12WT	Architectural LED Emergency Light with Photocell	White	120/277



ERHR Series

Indoor/Outdoor LED Remote Heads

ORDERING INFORMATION

CATALOG #	DESCRIPTION	VOLTAGE	TOTAL WATTAGE
ERHR12	Single Remote Head - Indoor/Outdoor	3.6 Volts	1.17 Watts
ERHR22	Double Remote Head - Indoor/Outdoor	3.6 Volts	2.34 Watts