

Catalog Number: EXA035A3500
Product ID: 7TAA140100R0308
UPC Number: 78378646926
Status: Active

Extra-flexible Connector. 1 Hole NEMA Standard 350 Ampacity 500 mm Long



Representative



Line Art

North American Specifications (UNSPSC)

UNSPSC	39121465 Flexible braid
IGCC	4695 Flexible braid
Brand Name	Blackburn
Type	Extra Flexible Braid Connector - 1-Hole
Special Features	1 Hole Nema Pads
Application	Suitable wherever it is necessary to take up expansion, severe vibration and/or misalignment when connecting Transformers, Switchgear, Generators or Busbars. Extra-Flexible Links for Heavy-Duty Applications.
Standard	IEEE / ANSI C37, 34
Conductor Material	Tin-Plated Copper
Cable Width	38 mm
Cable Length	500 mm
Conductor Category	Flexible
Shape Of Conductor	Flat

European Specifications (ETIM)

ETIM	EC000839 Braid wire
Conductor material	Cu, tinned
Conductor category	Class 6 = very flexible
Shape of conductor	Flat
Cable height approx.	500mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	0.01 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com