



BIBD6004MT, Double Sided Mounted Four Conductor Clear Insulated Mult-Tap Connector

By Burndy

Catalog # [BIBD6004MT](#)

Aluminum Multiple Tap Connector w/ Mount Holes, Clear Insulated, 4 Port, 2 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

Application


For Indoor Use Only, Copper Or Stranded Aluminum, Mountable

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil
Conductor - AL Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil



Conductor - AL Str Size Range	4 AWG - 600 kcmil
Conductor Size	4 AWG-600 KCMIL
Conductor - Copper Str Size Range	4 AWG - 600 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Screws	6
Connector Type	Multi Tap
Number Of Ports	4

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - L Length Overall mm	199 mm
Dimension - Height fraction	2.875 in
Dimension - Height inch	2.88 in
Dimension - Height mm	73.2 mm
Dimension - Width inch	3.00 in
Dimension - Width mm	76 mm
Dimension - Length Overall inch	7.84 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIBD-MT, Multi-Port
UPC 12 Digit	781810253403
UPC 14 Digit GTIN	00781810253403
Material	Aluminum
Hex Key	3/8
Plating Type	Unplated
UPC	781810253403

Logistics

Minimum Pack Quantity	1
-----------------------	---

Carton Quantity 20
Pallet Quantity 480

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)

Operational

Temperature Rating 194



A Hubbell brand