



BIBS3505DB, Direct Burial Submersible Five Conductor Insulated Multi-Tap Connector

By Burndy
Catalog # BIBS3505DB

Multi Port Direct Burial, 5 Ports, 350 kcmil-12 AWG Str, 600 V

Features

- Dual rated for aluminum or copper conductors
- Each unit individually marked for ease of identification
- Supplied with aluminum set-screws
- Supplied with oxide inhibitor pre-installed
- Submersible rated and suitable for Direct Burial

Application

For Outside Direct Burial

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - AL Str Size Range	12 AWG - 350 kcmil
Conductor Size	12 AWG-350 KCMIL
Conductor - Copper Str Size Range	12 AWG - 350 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Connector Type	Multi Tap
Number Of Ports	5

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions



Dimension - L Length Overall mm	158 mm
Dimension - Height inch	2.46 in
Dimension - Height mm	62 mm
Dimension - Strip Length inch	1.125
Dimension - Width inch	4.06 in
Dimension - Width mm	103 mm
Dimension - Length Overall inch	6.24 in

Force Related

Installation Torque Recommended in-lb	450 LBS/in
---------------------------------------	------------

General

Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Plated	N
Type	BIBS, Multi-Port - Direct Burial
UPC 12 Digit	781810523612
UPC 14 Digit GTIN	00781810523612
Material	Aluminum
Plating Type	Unplated
UPC	781810523612

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	672

Operational

Temperature Rating	194
--------------------	-----

Product Assets

- [Catalog \[English\]](#)
[Catalog \[English\]](#)