

BITO250, Opposite Side Two Conductor Clear Insulated Multi-Tap Connector

By Burndy
Catalog # [BITO250](#)



Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 2 Sided Entry, 10 AWG-250 kcmil, Al/Cu Rated, 2.03 L, 2.13 H

Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - AL Str Size Range	10 AWG - 250 kcmil
Conductor Size	10 AWG-250 KCMIL
Conductor - Copper Str Size Range	10 AWG - 250 kcmil
Conductor Type	AL C Str-Size;CU C Str-Size

Configuration

Physical Attribute - Number of Screws	2
Connector Type	Multi Tap
Number Of Ports	2

Current

Voltage - Maximum	600 V
Operating Voltage	600 V

Dimensions

Dimension - L Length Overall mm	52 mm
Dimension - Height fraction	2.125 in
Dimension - Height inch	2.13 in
Dimension - Height mm	54.10 mm
Dimension - Width inch	2.64 in
Dimension - Width mm	67 mm
Dimension - Length Overall inch	2.03 in

General

Material - Hardware	Aluminum
Insulation Type	Plastisol
Trade Name	UNITAP™
Insulation	Y
Sub Brand	UNITAP
Physical Attribute - Screw Type	Allen
Plated	N
Type	BIT
UPC 12 Digit	781810134078
UPC 14 Digit GTIN	00781810134078
Material	Aluminum
Hex Key	5/16 in
Plating Type	Unplated
UPC	781810134078

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	3200

Operational

Temperature Rating	90°C
--------------------	------

Product Assets

[Catalog \[English\]](#)
[Catalog \[English\]](#)