



GAR1626, Mech Grounding Connector, Cable to Rod or Pipe

By Burndy
Catalog # [GAR1626](#)

Mechanical Grounding Connector, Cable to Rod or Pipe, 4 AWG (Sol)-2/0 AWG (Str), 1-1/4" Pipe, 1-3/8"-1-1/2" Rod, #11 Rebar

Features

- Parallel or 90° Copper Cable Connection
- One-wrench installation
- Rated for Direct Burial in earth or concrete

Application


For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
Buy America(n) Qualified	BABA Compliant (All status valid till December 2026)
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Rebar Size	11
Conductor - Pipe or Round Tube Size Range	1-1/4 in
Conductor - Rebar Size Range	11
Conductor - Rod Size Range	1 3/8 in-1 1/2 in
Conductor - Copper Str Size	2/0 AWG
Conductor - Rod Size	1.380-1.66 in
Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG-3/0 AWG
Conductor Type	• CU C Solid-Size • CU C Str-Size • CU Tube Std-Size • Rod-Size
Conductor - Copper Str Size Range	5 AWG - 2/0 AWG
Conductor - Copper Tube Std Size Range	1/4 IPS IPS
Conductor - Copper Tube Std Size	1/4 IPS IPS



Dimensions

Package Height	0.000 in
Dimension - Height mm	88.9 mm
Dimension - Height inch	3.50 in
Dimension - Height fraction	3-1/2 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	40 mm
Dimension - Outside Diameter inch	1.66 in
Dimension - Width fraction	3 in
Dimension - Width mm	76 mm
Dimension - Width inch	3.00 in
Dimension - B Length inch	1.88 in
Dimension - Length Overall inch	1.56 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in
Installation Torque Recommended Run in-lb	240 Lb in

General

Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Cable(s) to Ground Rod/Pipe/Tube (GAR/GD/GK)>Single Conductor(GAR)
Material - Hardware Plated	DURIUM™ Silicon Bronze
Sub Brand	No
Product Type	MECHANICAL CONNECTOR
UPC	Mechanical
Type	781810233405
U Bolt Type	GAR
Material	204
Plating Type	Copper
UPC 12 Digit	Bright Dipped
UPC 14 Digit GTIN	781810233405
	00781810233405

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1500
Carton Quantity	30



A Hubbell brand