




GAR174C, Mech Grounding Connector, Cable to Rod or Pipe

By Burndy

Catalog # [GAR174C](#)

Mechanical Grounding Connector, Cable to Rod or Pipe, 8 AWG (Sol.) - 4 AWG (Str.), 1-5/8" to 1-7/8" Rod, 1-1/2" Pipe



Features

- Parallel or 90° Copper Cable Connection
- One-wrench installation
- Rated for Direct Burial in earth or concrete

Application

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

Specifications

Certification - UL Recognized	No
Buy American Compliant	Contact Manufacturer
Certification - cULus	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - Pipe or Round Tube Size Range	1-1/2 in
Conductor - Rod Size Range	1 5/8-1 7/8
Conductor - Copper Str Size	4 AWG
Conductor - Rod Size	1.620-1.90 in
Conductor - Copper Solid Size	8 AWG
Conductor - Copper Solid Size Range	8-3
Conductor Type	• CU C Solid-Size • CU C Str-Size • CU Tube Std-Size • Rod-Size
Conductor - Copper Str Size Range	9 AWG - 4 AWG
Conductor - Copper Tube Std Size Range	1 1/2
Conductor - Copper Tube Std Size	1 1/2

Dimensions

Package Height	0.000 in
Dimension - Height mm	101.6 mm

Dimension - Height inch	4.00 in
Dimension - Height fraction	4
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - L Length Overall mm	33 mm
Dimension - Outside Diameter inch	1.90 in
Dimension - Width fraction	3-1/4 in
Dimension - Width mm	83 mm
Dimension - Width inch	3.25 in
Dimension - B Length inch	2.31 in
Dimension - Length Overall inch	1.31 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in
Installation Torque Recommended Run in-lb	240 Lb in

General

Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Cable(s) to Ground Rod/Pipe/Tube (GAR/GD/GK)>Single Conductor(GAR)
Material - Hardware	DURIUM™ Silicon Bronze
Plated	No
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810234006
Type	GAR
U Bolt Type	268
Material	Copper
Plating Type	Bright Dipped
UPC 12 Digit	781810234006
UPC 14 Digit GTIN	00781810234006

Logistics

Minimum Pack Quantity	1
Pallet Quantity	1560
Carton Quantity	40

Product Assets

[Catalog \[English\]](#)

