



GB26, Mechanical Grounding Connector, Cable to Bar

By Burndy
Catalog # [GB26](#)

Mechanical Grounding Connector, Cable to 1/4" Thick Bar, 4 AWG (Sol)-2/0 AWG (Str), 3/8" Stud, 1-1/2 IN Width

Features

- High copper alloy ground connector for joining a range of cable to 1/4" thick bar
- Type GB separates cable from bar
- One-wrench installation
- UL467 Listed
- Suitable for Direct Burial in earth or concrete

Application


For Copper Cable To Bar, Direct Burial Cable

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Solid Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Size Range	4 AWG-2/0 AWG
Conductor - Copper Str Size Range	4 AWG - 2/0 AWG



Dimensions

Dimension - L Length Overall mm	24 mm
Dimension - Height inch	1.74 in
Dimension - Height mm	44.2 mm
Dimension - Width fraction	1-3/7 in
Dimension - Width inch	1.42 in
Dimension - Length Overall inch	0.94 in

Force Related

Installation Torque	240 lb-in
Recommended in-lb	

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Type	GB
UPC 12 Digit	781810231210
UPC 14 Digit GTIN	00781810231210
Material	Copper Alloy
Plating Type	Unplated
UPC	781810231210

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	6250

Product Assets

[Catalog \[English\]](#)