



GC2525CT, Mech Ground, One to Two Cables to Bar

By Burndy
Catalog # [GC2525CT](#)

Cast Copper Alloy Cable Tray Ground Clamp, #6 Sol. (.162 Dia.) -1/0 Str. (.372 Dia.), 1.12 in L, 1.45 in W, Tin Plated



Features

- Cable Tray Ground Clamp of tin-plated cast copper
- Accommodates either one or two conductors, copper or aluminum cable
- Low profile head with deep Phillips recess
- Galvanized steel bolt has ribbed neck preventing rotation during installation when installed in a 0.44 diameter hole
- Rated for Direct Burial in earth or concrete
- UL467 Listed for the US and Canadian Markets with copper conductor only

Application

For Direct Burial Applications In Concrete Or Earth And For Used With Aluminum Or Galvanized Steel Cable Tray

Specifications

Certification - UL Recognized	No
Buy American Compliant	No
Certification - cULus	No
Industry Standard(s)	UL467
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct Burial	Yes
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor - AL Str Size	• 6 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG
Conductor - AL Str Size Range	6 AWG-1/0 AWG
Conductor - Copper Str Size	• 7 AWG • 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0

Conductor - Copper Solid Size	• 6 AWG • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG
Conductor - Copper Solid Size Range	6 AWG-1/0 AWG
Conductor - Copper Str Size Range	7 AWG - 1/0 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	49.5 mm
Dimension - Height inch	1.95 in
Package Weight	0.000 lb.
Package Length	0.000 in
Package Width	0.000 in
Dimension - Width mm	37 mm
Dimension - Width inch	1.45 in
Dimension - B Length inch	1.12 in
Dimension - Cross Flats inch	0.56 in

Force Related

Installation Torque Recommended	240 lb-in in-lb
---------------------------------	-----------------

General

Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Cable Tray Ground Clamps
Plated	Yes
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810035504
Type	GC-CT
Material	Copper Alloy
Plating Type	Tin
UPC 12 Digit	781810035504
UPC 14 Digit GTIN	00781810035504

Logistics

Minimum Pack Quantity	1
-----------------------	---

Pallet Quantity 7200
Carton Quantity 50

Product Assets

[Catalog \[English\]](#)



A Hubbell brand