



GP64526G1, Mech Ground Conn, 2 Cables to Rod or Pipe

By Burndy
Catalog # [GP64526G1](#)

Raised Floor Grounding Clamp, 2 Cables to Rod or Pipe, 3/4-1" Round, 3/4"-7/8" Square, 4 Sol-2/0 Str

Features

- Accepts 1 or 2 ground conductors, requiring less connectors to install signal reference grid
- Copper alloy, DURIUM™ Silicon U-Bolts, Nuts and Lockwashers, proving a low impedance ground path for maximum performance
- Grounds all pedestals (Round or Square) from 3/4" to 1"
- UL467 Listed

Application

For Raised Floor Systems

Specifications

Buy American Compliant	Contact Manufacturer
Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance	EX
Status	
Certification - UL Listed Direct	No
Burial	
UL Listed	Yes
Certification - CSA Approved	No

Conductor

Conductor Size	#4 AWG Sol - 2/0 AWG Str
Number Of Conductors	• 1 • 2
Conductor - Copper Solid Size Range	4 AWG
Conductor Type	CU C Str-Size
Conductor - Copper Str Size Range	2/0 AWG

Dimensions

Package Height	0.000 in
Dimension - Height mm	0 mm
Package Weight	0.000 lb.
Package Length	0.000 in



Package Width	0.000 in
Dimension - L Length Overall mm	43 mm
Bolt Size	3/8 in
Dimension - Width mm	60 mm
Dimension - Width inch	2.38 in
Dimension - B Length inch	1.50 in
Dimension - Length Overall inch	1.69 in

Force Related

Installation Torque Recommended	240 LBS/in in-lb
---------------------------------	------------------

General

Product Family	Grounding and Bonding Connectors>Copper Mechanical Grounding Connectors>Pedestal Raised Floor Ground Clamp DURIUM™ Silicon Bronze
Material - Hardware	No
Plated	No
Pedestal Type	• Round • Square
Sub Brand	MECHANICAL CONNECTOR
Product Type	Mechanical
UPC	781810828014
Type	GP-G1
U Bolt Type	UB222
Material	Copper Alloy, Cast
Plating Type	Unplated
UPC 12 Digit	781810828014
UPC 14 Digit GTIN	00781810828014

Logistics

Minimum Pack Quantity	1
Pallet Quantity	2400
Carton Quantity	12

Product Assets

[Catalog \[English\]](#)