



HSC100FR, Heat Shrink Tubing, 1" ID Min.  
(Exp.), 0.5" ID Max.(Rec.), 1/0-4/0 Flex,  
PVC, Flame Retardant, Clear, 600V.

By Burndy  
Catalog # [HSC100FR](#)

Heat shrink tubing, Conductor range: 4/0-3/0 (Code), 1/0-4/0 (Flex)

Features

- Flame Retardant
- Flexible Polyvinylchloride
- 2:1 Shrink Ratio
- 600 Volts

Application

Used on UL Recognized TO 600V

Specifications

|                              |     |
|------------------------------|-----|
| Buy American Compliant       | No  |
| EU RoHS Indicator            | Yes |
| Certification - ETL          | No  |
| Standards - RoHS Compliance  | CM  |
| Status                       |     |
| Certification - CSA Approved | Yes |
| UL Listed                    | No  |

Conductor

|                 |                      |
|-----------------|----------------------|
| Conductor Size  | 4/0AWG - 300kcmil    |
| Conductor Range | #1/0 AWG to #4/0 AWG |

Configuration



Connector Type                      CLEAR TUBES

Dimensions

|            |                      |
|------------|----------------------|
| Length     | 300 in               |
| Width      | 1 in                 |
| Height     | 1 in                 |
| Dimensions | 300 in x 1 in x 1 in |

General

|            |                        |
|------------|------------------------|
| Sub Brand  | VISISHRINK             |
| Trade Name | VISI-SHRINK™           |
| Color      | Clear                  |
| Type       | HSC-FR, Fire Retardant |
| Material   | Polyvinyl chloride     |
| UPC        | 781810266120           |

Logistics

|                       |     |
|-----------------------|-----|
| Minimum Pack Quantity | 1   |
| Carton Quantity       | 10  |
| Pallet Quantity       | 360 |

Product Assets

[Catalog \[English\]](#)