



K11A39U2, Aluminum Universal Terminal, 2 Hole, Two: 1/0 AWG (Str)-750 kcmil, 3/8" Stud, 1.38" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated.

By Burndy
Catalog # [K11A39U2](#)

Aluminum Universal Terminal, 2 Hole, 1/0 AWG (Str)-750 kcmil

Features

- Dual rated panelboard lugs
- Constructed from high strength, extruded aluminum alloy
- Electro tin-plated to provide low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	NC
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil
Conductor - AL Str Size	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil;636 kcmil;650 kcmil;700 kcmil;715 kcmil;750 kcmil
Conductor - AL Str Size Range	1/0 AWG (Str)-750 kcmil
Conductor - Copper Solid Size	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	1/0 AWG-4/0 AWG
Number Of Conductors	2
Conductor Size	1/0 AWG-750 KCMIL
Conductor - Copper Str Size Range	1/0 AWG (Str)-750 kcmil



Conductor Type	AL C Str-Size;CU C Str-Size;CU C Solid-Size
----------------	---

Configuration

Physical Attribute - Number of Holes	2
Connector Type	Stacked

Dimensions

Dimension - L Length Overall mm	125 mm
Dimension - Pad Width inch	1.52 in
Dimension - Height fraction	3 in
Dimension - Height inch	3.02 in
Dimension - Height mm	76.7 mm
Dimension - Hole Size inch	0.41 in
Dimension - Hole Size mm	10 mm
Dimension - Screw Size inch	13/16
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8 in
Dimension - Width fraction	1-69/100 in
Dimension - Width inch	1.52 in
Dimension - Width mm	43 mm
Dimension - Bolt Hole Size inch	0.38 in
Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	4.91 in
Dimension - D inch	2.31 in
Dimension - N inch	0.38 in

Force Related

Installation Torque Recommended in-lb	375 LBS/in
---------------------------------------	------------

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type Plated	Allen Y
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810370292
UPC 14 Digit GTIN	00781810370292
Material	Aluminum
Hex Key	3/8

Plating Type

UPC

Tin plated

781810370292

Operational

Temperature Rating

194

Logistics

Minimum Pack Quantity

Carton Quantity

Pallet Quantity

1

18

576

Product Assets

[Catalog \[English\]](#)

