



K3A36U2N, AL Universal Terminal, 3 Conductor, #2 AWG Str-600 kcmil, 1/2" Stud, 1.75" Spacing, 3 Screws, Al/Cu Rated

By Burndy
Catalog # K3A36U2N

Aluminum Universal Terminal, 3 Conductor, 2 AWG (Str)-600 kcmil

Features

- Dual rated lugs
- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

Application

For Aluminum and Copper Conductors

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	• Buy America Compliant (All status valid till December 2025) • Buy American Act Compliant (All status valid till December 2025) • BABA Compliant (All status valid till December 2025)
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	• 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 300 kcmil • 350 kcmil • 400 kcmil • 450 kcmil • 500 kcmil • 550 kcmil • 600 kcmil
-----------------------------	---



Conductor - AL Str Size	• 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil • 266 kcmil • 300 kcmil • 336 kcmil • 350 kcmil • 397 kcmil • 400 kcmil • 450 kcmil • 477 kcmil • 500 kcmil • 550 kcmil • 556 kcmil • 600 kcmil
Conductor - AL Str Size Range	2 Str. - 600 Kcmil
Number Of Conductors	3
Conductor Size	2 AWG-600 KCMIL
Conductor - Copper Str Size Range	2 Str. - 600 Kcmil
Conductor Type	• AL C Str-Size • CU C Str-Size

Configuration

Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	3
Connector Type	Parallel Set-Screw

Dimensions

Dimension - L Length Overall mm	119.12 mm
Dimension - Pad Width inch	3.64 in
Dimension - Height fraction	1.5555555555555556 in
Dimension - Height inch	1.56 in
Dimension - Height mm	39.6 mm
Dimension - Hole Size fraction	9/16
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - Stud Size inch	1/2 in

Dimension - Width fraction	3-63/100 in
Dimension - Width inch	3.64 in
Dimension - Width mm	92 mm
Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	1/2
Dimension - Length Overall inch	4.69 in
Dimension - D inch	3.22 in
Dimension - N inch	0.63 in

Force Related

Installation Torque	375 LBS/in
Recommended in-lb	

General

Material - Hardware	Aluminum
Sub Brand	UNIVERSAL TERM
Physical Attribute - Screw Type	Slot



A Hubbell brand

Plated	Y
Type	Bolted Lugs & Terminals
UPC 12 Digit	781810601204
UPC 14 Digit GTIN	00781810601204
Material	Aluminum
Plating Type	Tin plated
UPC	781810601204

Logistics

Minimum Pack Quantity	1
Carton Quantity	36
Pallet Quantity	1152

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)