



KVS26, 2-piece OKLIP Service Connector for heavy duty applications

By Burndy
Catalog # [KVS26](#)

Compact 2-piece, high strength, copper alloy with neoprene rings

Features

- Compact, 2-piece, high strength, high copper alloy, recommended for heavy duty connections
- Neoprene rings hold silicon bronze bolts in place during installation
- Installed with ordinary wrench

Application

For Copper, Copperweld

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	RUS
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	RUS
Certification - CSA Approved	EX
UL Listed	No
	Yes

Conductor

Conductor - Copper Solid Tap	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Tap Range	6 AWG-2/0 AWG
Conductor - Copper Str Run Range	1 str. 2/0 str.
Conductor - Copper Str Tap Range	6 str. - 2/0 str.
Conductor Type	CU C Str-Run;CU C Str-Tap;CU Weld C Solid-Run;CU Weld C



Conductor - CopperWeld Solid Run	Solid-Tap 3/0
Conductor - CopperWeld Solid Tap	3/0

Dimensions

Dimension - Pad Width inch	1.06 in
Dimension - Height inch	1.74 in
Dimension - Height mm	44.20 mm
Dimension - Stud Size inch	5/16 in
Dimension - Width inch	1.56 in
Dimension - Width mm	40 mm

Force Related

Installation Torque	180 LBS/in
Recommended in-lb	

General

Trade Name	OKLIP™
Sub Brand	OKLIP
Plated	N
Type	KVS, Compact
UPC 12 Digit	781810061206
UPC 14 Digit GTIN	00781810061206
Material	Copper
Plating Type	Unplated
UPC	781810061206

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	6000

Product Assets

[Catalog \[English\]](#)