



YAV25L2NT14FX90, Compression Terminal, 1/0 Flex G, H, I, K, M, DLO, 1/0 AWG (B/C), CU, 2-Hole, 1/4" Stud, 5/8" Spacing, Narrow Tongue, 90 Degree

By Burndy
Catalog # [YAV25L2NT14FX90](#)

Copper Compression Lug, Narrow Tongue, 2 Holes W/ Inspection Window, 1/0 AWG, 1/4" Stud, 12 index, Pink, Tin plated, 90 Degree

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

General

Catalog Number	YAV25L2NT14FX90
Color	Pink
Color Code	Pink
Connector Type	STANDARD BARREL
Construction Material - Main	Copper
Die Index	12
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	• Chamfered • Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Number of Holes	2
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin
Sub Brand	HYLUG
Trade Name	HYLUG™
Type	Narrow Tongue
UPC	781810660843
UPC 14 Digit GTIN	00781810660843

Dimensions

Dimension - B Length fraction 11/16 in



Dimension - B Length inch	0.69 in
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - L Length Overall mm	42 mm
Dimension - Length Overall inch	1.66 in
Dimension - N inch	0.31 in
Dimension - Outside Diameter inch	0.56 in
Dimension - Pad Width inch	0.64 in
Dimension - Strip Length inch	11/16 in
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4 in
Physical Attribute - Tongue Angle	90 Degree

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper DLO Size	1/0 AWG
Conductor - Copper DLO Size Range	1/0 AWG
Conductor - Copper Flex G Size	"1/0 AWG"
Conductor - Copper Flex G Size Range	1/0 AWG
Conductor - Copper Flex H Size	"1/0 AWG"
Conductor - Copper Flex H Size Range	1/0 AWG
Conductor - Copper Flex I Size	"1/0 AWG"
Conductor - Copper Flex I Size Range	1/0 AWG

Conductor - Copper Flex K Size	"1/0 AWG"
Conductor - Copper Flex K Size	1/0 AWG
Range	
Conductor - Copper Flex M	"1/0 AWG"
Size	
Conductor - Copper Str	"1/0 AWG"
Compact Size	
Conductor - Copper Str Navy	100
Size	
Conductor - Copper Str Navy	100 (61) Navy
Size Range	
Conductor - Copper Str Size	"1/0 AWG"
Conductor - Copper Str Size	1/0 AWG
Range	
Conductor - Material	COPPER
Conductor Size	1/0 AWG
Conductor Type	CODE/FLEX
Wire Size	1/0 AWG

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
--------------------------	---

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	24000

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Sales Drawings - 50035189](#)
- [Specifications - YAV25L2NT14FX90](#)
- [Video - HYDENT Compression Terminal Overview Video](#)



A Hubbell brand