



YAV26LTC14FX, Compression Terminal, 2/0 Flex G,H,I,K,M, DLO, 2/0 AWG, Cu, 1-Hole, 1/4" Stud, Standard Barrel

By Burndy

Catalog # [YAV26LTC14FX](#)

2/0 Flex G,H,I,K,M,DLO, 2/0 AWG, CU, 1 Hole, 1/4 Stud, Standard Barrel, Inspection Window

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2/0 AWG
Conductor - Copper Str Size	"2/0 AWG"
Conductor - Copper Flex I Size	2/0 AWG
Range	
Conductor - Copper Flex K Size	"2/0 AWG"
Conductor - Copper Flex K Size	2/0 AWG
Range	
Conductor - Copper Flex M Size	"2/0 AWG"
Conductor - Copper Str	"2/0 AWG"
Compact Size	
Conductor - Copper DLO Size	2/0 AWG
Conductor - Copper DLO Size	2/0 AWG
Range	
Conductor - Copper Flex G Size	"2/0 AWG"
Conductor - Copper Str Navy	125
Size	
Conductor - Copper Flex G Size	2/0 AWG
Range	



Conductor - Copper Str Navy	125 (61) Navy
Size Range	
Conductor - Copper Flex H Size	"2/0 AWG"
Conductor Size	2/0 AWG
Conductor - Copper Str Size	2/0 AWG
Range	
Conductor - Copper Flex H Size	2/0 AWG
Range	
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"2/0 AWG"
Conductor - CopperWeld Str	2/0 F AWG;2/0 G AWG;2/0 J AWG;2/0 K AWG;2/0 V AWG
Size	

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.63 in
Dimension - L Length Overall mm	49 mm
Dimension - Pad Width inch	0.93 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	13/16
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4
Dimension - B Length inch	0.81 in
Dimension - Z inch	0.33 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25
Dimension - Length Overall inch	1.92 in
Dimension - N inch	0.31 in

General

Die Index	13
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Black
Physical Attribute - Tongue Type	Standard
Plated	Yes
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	Standard Barrel, Tin Plated
UPC 12 Digit	781810022658
UPC 14 Digit GTIN	00781810022658
Material	COPPER

Plating Type	Tin
Finish Type	Tin-Plated
UPC	781810022658

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	29000

Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand