



YAV2CL2TC14FX, Cu Compression, 2-Hole,
1/4" Stud, 5/8" Spacing, Standard Barrel, 2
Flex

By Burndy
Catalog # [YAV2CL2TC14FX](#)

2 Flex G,H,I,K,M,DLO, 2 AWG, CU, 2 Hole, 1/4 Stud, 5/8 IN
Spacing, Standard Barrel, Inspection Window

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2 AWG
Conductor - Copper Str Size	"2 AWG"
Conductor - Copper Flex I Size	2 AWG
Range	
Conductor - Copper Flex K Size	"2 AWG"
Conductor - Copper Flex K Size	2 AWG
Range	
Conductor - Copper Flex M Size	"2 AWG"
Conductor - Copper Solid Size	2 AWG
Conductor - Copper Str	"2 AWG"
Compact Size	
Conductor - Copper DLO Size	2 AWG
Conductor - Copper DLO Size	2 AWG
Range	
Conductor - Copper Flex G Size	"2 AWG"
Conductor - Copper Str Navy	60
Size	



Conductor - Copper Flex G Size	2 AWG
Range	
Conductor - Copper Str Navy	60 (37) Navy
Size Range	
Conductor - Copper Flex H Size	"2 AWG"
Conductor Size	2 AWG
Conductor - Copper Str Size	2 AWG
Range	
Conductor - Copper Flex H Size	2 AWG
Range	
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"2 AWG"
Conductor - CopperWeld Str	2 A AWG;2 F AWG;2 G AWG;2 J
Size	AWG;2 K AWG;2 N AWG;2 P
	AWG

Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.46 in
Dimension - L Length Overall mm	57 mm
Dimension - Pad Width inch	0.68 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	11/16
Dimension - Stud Size fraction	1/4
Dimension - B Length fraction	5/8 in
Dimension - B Length inch	0.63 in
Dimension - Z inch	0.34 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25

Dimension - Length Overall	2.26 in	UPC 12 Digit	781810022207
inch		UPC 14 Digit GTIN	00781810022207
Dimension - N inch	0.31 in	Material	COPPER
General		Plating Type	Tin - Electro Plated
		Finish Type	Tin-Plated
		UPC	781810022207
		Logistics	
		Minimum Pack Quantity	1
		Carton Quantity	25
		Product Assets	
		Catalog [English]	
		Installation Manual [English]	
		Installation Manual [English]	
Die Index	10		
Trade Name	HYLUG™		
Sub Brand	HYLUG		
Color Code	Brown		
Physical Attribute - Tongue	Standard		
Type			
Plated	Y		
Feature - Barrel Type	Standard		
Feature - Barrel Style	Chamfered		
Type	Standard Barrel, Tin Plated		



A Hubbell brand