



YAZ442NT38FX, Cu Compression, 2-Hole, 3/8" Stud, 1" Spacing, Long Barrel, Narrow Tongue, 750 kcmil G, H, 777 DLO

By Burndy

Catalog # [YAZ442NT38FX](#)

750 kcmil G,H,777 DLO, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Long Barrel, Inspection Window

Features

- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damaging of the strands
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL 486A-486B
Certification - ETL	Contact Manufacturer
Standards - RoHS Compliance Status	No
Certification - CSA Approved	CM
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	750 KCMIL
Conductor - Copper Str Size	750 KCMIL
Conductor - Copper Flex I Size Range	750 kcmil
Conductor - Copper Flex K Size	750
Conductor - Copper Flex M Size	750
Conductor - Copper DLO Size	777 KCMIL
Conductor - Copper DLO Size Range	777 kcmil
Conductor - Copper Flex G Size	750 KCMIL
Conductor - Copper Flex G Size Range	750 kcmil
Conductor - Copper Flex H Size	750 KCMIL
Conductor Size	750 KCMIL
Conductor - Copper Str Size Range	750 kcmil



Conductor - Copper Flex H Size Range	750 kcmil
Conductor Type	FLEX
Conductor - Copper Flex I Size	750 KCMIL

Configuration

Physical Attribute - Number of Holes	2
Connector Type	LONG BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	1.50 in
Dimension - L Length Overall mm	155 mm
Dimension - Pad Width inch	1.62 in
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	3-1/16
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8 in
Dimension - B Length fraction	3 in
Dimension - B Length inch	3.00 in
Dimension - Z inch	0.53 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	6.09 in
Dimension - Length Side B inch	6.08 in
Dimension - Diameter Min Size inch	2.03 in
Dimension - N inch	0.50 in

General

Die Index	L115
Trade Name	HYLUG™

Sub Brand	HYLUG	UPC	781810166178
Color Code	Yellow		
Plated	Y	Logistics	
Feature - Barrel Type	Long	Minimum Pack Quantity	1
Feature - Barrel Style	Chamfered	Carton Quantity	25
Type	YAZ-2-NTFX, Long Barrel	Pallet Quantity	1800
	Narrow Tongue		
UPC 14 Digit GTIN	00781810166178	Product Assets	
Material	COPPER	Catalog [English]	
Plating Type	Tin - Electro Plated	Installation Manual [English]	
Finish Type	Tin-Plated	Installation Manual [French, English]	



A Hubbell brand