



YAZV252TC14FX, Cu Compression, 2-Hole, 1/4" Stud, 5/8" Spacing, Long Barrel, 1/0 Flex G, H, I, K, M, DLO, 1/0 AWG B, C

By Burndy

Catalog # [YAZV252TC14FX](#)

1/0 Flex G,H,I,K,M,DLO, 1/0 AWG (B/C), CU, 2 Hole, 1/4 Stud, 5/8 IN Spacing, Long Barrel, Inspection Window

Features

- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damaging of the strands
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	1/0 AWG
Conductor - Copper Str Size	"1/0 AWG"
Conductor - Copper Flex I Size Range	1/0 AWG
Conductor - Copper Flex K Size	"1/0 AWG"
Conductor - Copper Flex K Size Range	1/0 AWG
Conductor - Copper Flex M Size	"1/0 AWG"
Conductor - Copper Str Compact Size	"1/0 AWG"
Conductor - Copper DLO Size	1/0 AWG
Conductor - Copper DLO Size Range	1/0 AWG
Conductor - Copper Flex G Size	"1/0 AWG"
Conductor - Copper Str Navy Size	100
Conductor - Copper Flex G Size Range	1/0 AWG



Conductor - Copper Flex H Size	"1/0 AWG"
Conductor Size	1/0 AWG
Conductor - Copper Str Size Range	1/0 AWG
Conductor - Copper Flex H Size Range	1/0 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"1/0 AWG"
Conductor - CopperWeld Str Size	1/0 F AWG;1/0 G AWG;1/0 J AWG;1/0 K AWG

Configuration

Physical Attribute - Number of Holes	2
Connector Type	LONG BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.56 inch
Dimension - L Length Overall mm	81 mm
Dimension - Pad Width inch	0.83 inch
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	1-9/16
Dimension - Stud Size fraction	1/4
Dimension - B Length fraction	1-1/2 in
Dimension - B Length inch	1.50 in
Dimension - Z inch	0.34 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25
Dimension - Length Overall inch	3.20 in
Dimension - Length Side B inch	3.20 in
Dimension - N inch	0.31 in

General

Die Index	12	Finish Type	Tin-Plated
Trade Name	HYLUG™	UPC	781810228395
Sub Brand	HYLUG		
Color Code	Pink	Logistics	
Plated	Y	Minimum Pack Quantity	1
Feature - Barrel Type	Long	Carton Quantity	50
Feature - Barrel Style	Chamfered;Skived	Pallet Quantity	23200
Type	Long Barrel, Skive		
UPC 12 Digit	781810228395	Product Assets	
UPC 14 Digit GTIN	00781810228395	Catalog [English]	
Material	COPPER	Installation Manual [English]	
Plating Type	Tin	Installation Manual [French, English]	



A Hubbell brand