



YGHC34C34 Compression Grounding C-TAP Connector

By Burndy
Catalog # [YGHC34C34](#)

Copper Compression C Connector, 300-500 kcmil (Run & Tap)

Features

- Irreversible compression ground tap figure C connector
- C-shaped opening permits placing two continuous parallel cables into conductor groove
- UL467 Listed
- Acceptable for direct burial in earth or concrete
- Prefilled with PENETROX™ compound and strip sealed

Application

For Direct Burial Cables

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	Direct Burial
Certification - ETL	No
Standards - Industry Standards Met	UL467;IEEE 837;UL468A-468B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Run	300;350;400;450;500
Conductor - Copper Str Run Range	300-500
Conductor - Copper Str Tap	300;350;400;450;500
Conductor - Copper Str Tap Range	300-500

Configuration

Physical Attribute - Number of	3
Crimps Required	
Connector Type	Tap

Dimensions

Dimension - L Length Overall	28 mm
Dimension - Height fraction	2-81/89 in
Dimension - Height inch	2.91 in
Dimension - Height mm	73.9 mm
Dimension - B Length inch	1.10 in
Dimension - Length Overall	1.10 in
inch	

General

Die Index	1011
Trade Name	HYTAP™
Sub Brand	HYGROUND, HYTAP
Plated	N
Type	Taps
UPC 12 Digit	781810221082
UPC 14 Digit GTIN	00781810221082
Material	Copper
Plating Type	Unplated
UPC	781810221082

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	2960

Product Assets

[Catalog \[English\]](#)