



YH3939WCC, Cu Compression H Tap and Clear Cover, 750-500 kcmil Run, 750-350 kcmil Tap

By Burndy

Catalog # [YH3939WCC](#)

Copper Compression H Tap, 750 KCMIL-500 KCMIL (Main), 750 KCMIL-350 KCMIL (Tap), Tin Plated

Features

- Uninsulated compression H-tap connector, tin-plated
- Designs with more than one tap wire groove require installers to utilize a minimum of one Main (Run) and one Tap groove, other grooves can be left empty
- 'Third Hand' is a string provided with the H-tap connector and is used to wrap the wire while being inserted into the run and tap grooves
- H-tap connectors can be purchased separately or kitted with covers
- YH is connector sold separately without cover
- YH-WC is kitted H-tap connector and black cover
- YH-WCC is kitted H-tap connector and clear cover

Application

Wire Tap

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Copper Flex I Tap	350;400;450;500
Conductor - Copper Flex I Tap Range	550 KCMIL-350 KCMIL
Conductor - Copper Flex K Run	450;500
Conductor - Copper Flex K Tap	350;400;450;500
Conductor - Copper Flex M Run	450;500
Conductor - Copper Flex M Tap	350;400;450;500
Conductor - Copper Flex G Run	450;500
Conductor - Copper Str Run	500;550;600;700;750
Conductor - Copper Flex G Tap	350;400;450;500
Conductor - Copper Str Run Range	750 KCMIL-500 KCMIL



Conductor - Copper Str Tap	350;400;450;500;550;600;700
Conductor - Copper Str Tap Range	750 KCMIL-350 KCMIL
Conductor - Copper Flex H Tap	350;400;450;500
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Run	550 KCMIL-450 KCMIL

Configuration

Connector Type	H-TAP W/CLR COVER
----------------	-------------------

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - L Length Overall mm	32 mm
Dimension - Strip Length inch	1-3/8
Dimension - Width inch	2.97 in
Dimension - Length Overall inch	1.25 in

General

Die Index	KR
Trade Name	CRIMPIT™
Sub Brand	CRIMPIT
Color Code	Yellow
Plated	Y
Type	Compression Taps
UPC 12 Digit	781810436493
UPC 14 Digit GTIN	00781810436493
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810436493

Logistics

Minimum Pack Quantity	1
Carton Quantity	5
Pallet Quantity	450

Operational

Temperature Rating	194
--------------------	-----



A Hubbell brand