



YP29C26, Figure 6-shaped Copper Tap Connector

By Burndy
Catalog # [YP29C26](#)




Figure 6 - shaped, wide range-taking CU compression tap connector for primary service taps and secondary service drops, Width: .75 IN, Die Index: D

Features

- Compression tap connector for primary service taps and secondary service drops
- Connector can be gripped in tool and slipped over the line for easy installation

Application

For Extra Wide Range Of Copper And Primary Service Taps And Secondary Service Drops

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No
Buy America(n) Qualified	Contact Manufacturer

Conductor

Conductor - Copper Str Run	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
Conductor - Copper Str Run Range	1/0 -250 kcmil
Conductor - Copper Str Tap	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	4 AWG-2/0 AWG

Configuration

Connector Type	Tap
----------------	-----

Dimensions

Dimension - L Length Overall mm	19 mm
Dimension - Height inch	2.00 in
Dimension - Height mm	51 mm
Dimension - Length Overall inch	1.00 in

General

Sub Brand	CRIMPIT
Die Index	D
Trade Name	CRIMPIT™
Plated	Y
Type	YP-C
UPC 12 Digit	781810118009
UPC 14 Digit GTIN	00781810118009
Material	Copper
Plating Type	Unplated
UPC	781810118009

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	8700

Product Assets

[Catalog \[English\]](#)