


# YSHG4429 Compression H-Tap Connector

By Burndy  
Catalog # [YSHG4429](#)

Copper Compression Double H- Tap Connector, 2 AWG - 250 kcmil (Tap), #8 & #9 Rebar/ 1" Ground Rod



**Features**

- UL467 Listed
- Suitable for direct burial in earth or concrete
- High conductivity copper extrusion minimizes resistance and eliminates corrosion due to dissimilar metals
- Grooves are prefilled with PENETROX™ E2 oxide inhibitor and individually sealed inhibiting moisture and contaminants

**Application**

For Direct Burial In Earth Or Concrete

**Specifications**

|                                         |                       |
|-----------------------------------------|-----------------------|
| Buy American Compliant                  | No                    |
| Certification - cULus                   | No                    |
| EU RoHS Indicator                       | Yes                   |
| Certification - UL Recognized           | No                    |
| Industry Standard(s)                    | UL 467, Direct Burial |
| Certification - ETL                     | No                    |
| Standards - Industry Standards Met      | UL467                 |
| Standards - RoHS Compliance Status      | CM                    |
| Certification - CSA Approved            | No                    |
| UL Listed                               | Yes                   |
| Certification - UL Listed Direct Burial | Yes                   |

**Conductor**

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Conductor - Rebar Run       | 8 ;9                                            |
| Conductor - Rebar Run Range | 8 -9                                            |
| Conductor - Rod Run         | 1 in                                            |
| Conductor - Rod Run Range   | 1 in                                            |
| Conductor - Copper Str Tap  | 2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 |

|                                  |                          |
|----------------------------------|--------------------------|
| Conductor - Copper Str Tap Range | kcmil<br>2 AWG-250 kcmil |
|----------------------------------|--------------------------|

**Configuration**

|                |       |
|----------------|-------|
| Connector Type | H-Tap |
|----------------|-------|

**Dimensions**

|                                 |         |
|---------------------------------|---------|
| Dimension - Height mm           | 0 mm    |
| Dimension - Width inch          | 3.22 in |
| Dimension - Width mm            | 82 mm   |
| Dimension - Length Overall inch | 2.44 in |

**General**

|                   |                |
|-------------------|----------------|
| Die Index         | KR             |
| Trade Name        | HYGROUND®      |
| Sub Brand         | CRIMPIT        |
| Plated            | N              |
| Type              | Taps           |
| UPC 12 Digit      | 781810128657   |
| UPC 14 Digit GTIN | 00781810128657 |
| Material          | Copper         |
| Plating Type      | Unplated       |
| UPC               | 781810128657   |

**Logistics**

|                       |      |
|-----------------------|------|
| Minimum Pack Quantity | 1    |
| Carton Quantity       | 20   |
| Pallet Quantity       | 1440 |

**Product Assets**

[Catalog \[English\]](#)