



15 kV, 110 kV BIL, Type C Standard Porcelain Cutout w/100A 10kAIC fuseholder

By Chance
Catalog # [C710112PB](#)

15 kV, 110 kV BIL, Standard Type C Porcelain Cutout with a 100A, 10kAIC fuseholder, parallel-groove connector and a NEMA "B" crossarm bracket.

Features

- Fully Compliant with ANSI/IEEE C37.41 & C37.42 – 2016
- Interchangeable with ABB Type ICX & S&C(MPS) Type XS
- Single Vent Solid Cap Design
- Uses Universal Style Fuse Links
- Synthetic Arc Quenching Fuse Holder Liner Material

Specifications

EU RoHS Indicator	No
Buy America(n) Qualified	Contact Manufacturer

Configuration


Bracket Type	NEMA "B" Heavy Duty for crossarm
--------------	----------------------------------

Current

Fuselink Current Range	1A to 100A
BIL	110 kV
Current Rating	100 A
Voltage - Radio Interference	Ambient @ 9.41kV
Creep and Leakage Distance	8.7" (220mm)
Reference Voltage Limit - Minimum	Thru 14.4kV
Voltage Rating	15 kV

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)



Temperature Rise - Max. at 300A	38° C
Voltage - Maximum	15 kV

Dimensions

Length	14.880 in
Weight	17.836 lb.
Height	4.130 in
Width	14.500 in
Dimensions	14.880 in x 14.500 in x 4.130 in

General

Material type	Standard
UPC	096359029014
Type	Cutout
Description - Replacement Fuse Holder	T710-112T

Logistics

Pallet Quantity	72
Carton Quantity	1
Standard Package	1

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)