



**CONSTRUCTION
ELECTRICAL
PRODUCTS**

60W & 100W LED Bay Lights



CL60LED



CL100LED

New



CL100LEDG2
&
CL60LEDG2

- CL100LED Length = 13 1/2", Diameter = 6 3/4"
- CL60LED Length = 13 7/16", Diameter = 5 1/32"
- 5000K $\pm$ 10%
- 6' 18/3 SJTW Power Cord w/NEMA 5-15 Plug
- Operating Temperature = -20F (-29C) to Max 140F (60C)
- UL Listed for Damp Locations
- RoHS Compliant
- 300 degree beam spread
- 60W and 100W ratings allow for substantial KWH rate savings over traditional Metal Halide fixtures
- Impact Resistant design gives these units the durability to withstand storage, transportation and demanding job site environments



Catalog Number	Description
CL60LED	60W, 7,200 Lumen LED High Bay
CL100LED	100W, 12,000 Lumen LED High Bay
CL100LEDG2	100W, 12,000 Lumen LED High Bay Improved Luminous Flux and 1 Foot Feed-Thru Cord
CL60LEDG2	60W, 7200 Lumen LED High Bay Improved Luminous Flux and 1 Foot Feed-Thru Cord



CEPnow.com

800.678.3470



7800 Las Positas Rd.
Livermore, CA 94551

t: 925-828-9420

f: 925-828-3416

reorder:led_worklight-613.pdf