

Catalog Number: J6-222666-15L
Product ID: 7TAA122020R0321
UPC Number: 07511435501
Status: Active



Representative

15kV, 200/600 Amp Multipoint Junction. 6-Points, Three 200 Amp Deepwell Interfaces, Three 600 Amp Bushing Interfaces, 15 kV, Standard 4 inch Spacing, Left Parking Stand Only

North American Specifications (UNSPSC)

UNSPSC	26121630 Cable accessories
IGCC	1779 Cable accessories
Brand Name	Elastimold
Type	Multi-Point Junction - 6 Points
Special Features	4 inch Center Spacing. Left Parking Stand.
Application	Suited for Subsurface, Vault or Padmount Applications and can be used for Sectionalizing, Looping, Tapping and Equipment Bypass.
Standard	ANSI/IEEE Standard 386
Size	Overall Length 31 inches, Width 6-3/4 inches.
Material	EPDM Rubber and Stainless Steel Mounting Brackets.
Temperature Rating	-40 to +65 Degrees C.
Mounting	Left Parking Stand.
Connection	Push-in

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com