



Representative Image

**Catalog No. TEYF315****Description: TEYF 3 POLE 15 AMP****UPC No 783164388473****Home > Circuit Breakers > Molded Case Circuit Breakers > Lighting Panel Circuit Breakers**

The TEyF is a one-inch wide per pole, compact, "bolt-on" circuit breaker for use on grounded 480y/277 Vac systems. The bolt-on mounting base accessory makes the TEyF suitable for varied applications as a lug-lug breaker. All TEyF circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. TEyF breakers are available in 1, 2, and 3 pole versions and can be ordered with auxiliary contact and shunt trip accessories. TEYF 3 POLE 15 AMP

**Descriptors**

|              |                                 |
|--------------|---------------------------------|
| Category     | Lighting Panel Circuit Breakers |
| Product Line | TEY / Q-Line (Bolt-On)          |
| GO Schedule  | EY                              |

**Specifications**

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Trip Style                      | Non-Interchangeable                              |
| Poles                           | 3                                                |
| Amperage                        | 15 A                                             |
| System Voltage                  | 120/240 Vac<br>240 Vac<br>277 Vac<br>480/277 Vac |
| Frame Type                      | TEYF                                             |
| 120/240 Vac Interrupting Rating | 65 KAIC                                          |
| 240 Vac Interrupting Rating     | 65 KAIC                                          |
| 277 Vac Interrupting Rating     | 18 KAIC                                          |
| 480/277 Vac Interrupting Rating | 18 KAIC                                          |
| Trip Function                   | LI                                               |
| Continuous Current Rated        | Standard                                         |
| Suitable for Reverse Feed       | Yes                                              |
| Long Time                       | Fixed                                            |
| Instantaneous                   | Fixed                                            |
| Current Metering                | No                                               |
| Protective Relays               | No                                               |
| Special Markings                | HACR                                             |
| Wire Range (Cu/Al)              | #14-#10                                          |
| GSA Compliance                  | No                                               |

**Classifications**

|           |         |
|-----------|---------|
| UL File # | E11592  |
| CSA File# | LR57114 |

  
**by ABB**

