

Kellems Wire Management, Deluxe Cord Grips, Straight Male, .250-.312", 3/8" with Mesh

Por Hubbell Wiring Device-Kellems
No de catálogo 07401001

Kellems Wire Management, Deluxe Cord Grips, Straight Male, .250-.312", 3/8" with Mesh

Características

- Stainless steel mesh is corrosion resistant
- Multiweave grip gives cable arc-of-bend control
- Endless weave provides easy cable/flexible conduit installation

Aplicación

Straight Male- Form 1

Rendimiento

Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting),
Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C,
Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C), Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Especificaciones

Industry Standard(s)	UL Listed
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.

Relacionado con conductores

Cable Size	.250"-.312" (.63-.79)
Cable Diameter Range	0.250 in-0.312 in
Conductor Range	0.25-0.312 in (.63-.79 mm)
Number Of Conductors	Single



Dimensiones

Thread Size	3/8" NPT
Display Size	3/8" NPT

General

Specifications	• Body - Aluminum • Bushing - Neoprene • Nut - Aluminum • Strand - Stainless Steel
Style	For Insulated Cables
UPC	783585321813
Type	Straight Male Thread
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Deluxe Cord Grips
Material	Aluminum Fittings, Stainless Steel Mesh
Series	Deluxe Cord Grips Series

Logística

Carton Quantity	5
-----------------	---

Operacional

Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
--------------------	---

Documentación del producto

[Catalog \[English\]](#)