

Kellems Wire Management, Deluxe Cord Grips, 90 Degree Male, 1.000-1.125", 1.50" with Mesh

By Hubbell Wiring Device-Kellems
Catalog # 074011045

Kellems Wire Management, Deluxe Cord Grips, 90 Degree Male, 1.000-1.125", 1.50" with Mesh

Features

- Stainless steel mesh is corrosion resistant
- Multiweave grip gives cable arc-of-bend control
- Endless weave provides easy cable/flexible conduit installation

Application

90 Degree Male- Form 5

Performance

Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting), Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C, Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C), Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Cable Size	1.000"-1.125" (2.54-2.86)
Cable Diameter Range	1.000 in-1.125 in



Conductor Range	1-1.125 in (2.54-2.86 mm)
-----------------	---------------------------

Dimensions

Display Size	1 1/2" NPT
Thread Size	1 1/2" NPT

General

Style	For Insulated Cables
Series	Deluxe Cord Grips Series
Specifications	• Body - Aluminum • Bushing - Neoprene • Nut - Aluminum • Strand - Stainless Steel
UPC	783585322995
Type	90 Degree Male Thread
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Deluxe Cord Grips
Material	Aluminum Fittings, Stainless Steel Mesh

Logistics

Carton Quantity	4
-----------------	---

Operational

Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
--------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)