

Kellems Wire Management, Deluxe Cord Grips, Straight Male, 2.062-2.187", 2" with Mesh

By Hubbell Wiring Device-Kellems
Catalog # [074011263](#)

Kellems Wire Management, Deluxe Cord Grips, Straight Male, 2.062-2.187", 2" with Mesh

Features

- Stainless steel mesh is corrosion resistant
- Multiweave grip gives cable arc-of-bend control
- Endless weave provides easy cable/flexible conduit installation
- UL514B Tray cable rated for dry locations

Application

Straight Male- Form 7

Performance

Environmental - Flammability - UL 94HB (Strand grip), UL 94V-2(Fitting), Environmental - Hazardous Locations - Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C, Environmental - Operating Temperatures - -30°F to +240°F (-34°C to +115°C), Environmental - Wet Locations - Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Sealing Ring Between Box And Fitting.
EU RoHS Indicator	Yes
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Cable Size	2.062"-2.187" (5.24-5.55)



Cable Diameter Range	2.062 in-2.187 in
Conductor Range	2.062-2.187 in (5.24-5.55 mm)

Dimensions

Display Size	2" NPT
Thread Size	2" NPT

General

Style	For Insulated Cables
Series	Deluxe Cord Grips Series
Specifications	• Body - Aluminum • Bushing - Neoprene • Nut - Aluminum • Strand - Stainless Steel
UPC	783585330907
Type	Straight Male Thread
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Deluxe Cord Grips
Material	Aluminum Fittings, Stainless Steel Mesh

Logistics

Pallet Quantity	180
Carton Quantity	20

Operational

Temperature Rating	Minimum -30 Deg F to 240 Deg F (-34 Deg C to 115 Deg C)
--------------------	---

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)