

Straight Blade Devices, Tamper Resistant
Receptacles, Duplex, Commercial/Industrial
Grade, 2-Pole 3-Wire Grounding, 15A 125V,
5-15R, Gray

By Hubbell Wiring Device-Kellems
Catalog # [5252GTR](#)

Straight Blade Devices, Tamper Resistant Receptacles, Duplex,
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A 125V,
5-15R, Gray

Features

- Tamper-resistant shutter complies with national electrical code requirements
- Smooth face
- Triple wipe contacts
- Wrap-around galvanized steel strap

Application

Hubbell-Pro Heavy Duty

Specifications

Nema Rating	5-15R
Industry Standard(s)	UL File No. E2186, Certified to CSA 22.2, No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant
Environmental Conditions	Indoor Dry unless protected by additional means

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Current

Amperage Rating	15 A
Voltage Rating	125 V
Wattage	1875 W



Connectivity	Back and Side Wired
Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Size	Standard Sized Product
------	------------------------

General

Color	Gray
Style	Smooth Face
Mounting Type	Screw Mount
UPC	783585582184
Type	Tamper Resistant Duplex
Material	Thermoplastic/Composite
Series	Hubbell-PRO

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum continuous 75°C • minimum -40°C (w/o impact)
--------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)