

Straight Blade Devices, Weather Resistant
Receptacles, Duplex, Commercial/Industrial
Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-
15R, Gray

By Hubbell Wiring Device-Kellems
Catalog # [5262GYWR](#)

Straight Blade Devices, Weather Resistant Receptacles, Duplex,
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A 125V, 5-
15R, Gray

Features

- Weather-resistance complies with national electrical code requirements
- Finder Groove Face
- Triple wipe contacts
- Compact design

Application

Hubbell-Pro Heavy Duty

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - Withstands 2,000V minimum, Environmental - Flammability - UL 94 V-2, Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact), Mechanical - Product Identification - Ratings are a permanent part of the device, Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only, Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

Specifications

Environmental Conditions	Weather Resistant
Nema Rating	5-15R
Industry Standard(s)	UL File No. E2186, Certified to CSA 22.2, No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Voltage Rating Description	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Rating	15 A
Voltage Rating	125 V
Wattage	1875 W
Connectivity	Back and Side Wired



Phase	Single Phase
Current / Amperage Rating	15 A

Dimensions

Length	3.28 in
Display Size	Standard Sized Product
Weight	0.2 lb.
Height	1.09 in
Width	1.41 in
Size	Standard Sized Product
Dimensions	3.28 in x 1.41 in x 1.09 in

General

Color	Gray
Style	Finder Groove Face
Series	Hubbell-PRO
Specifications	• Automatic Self-grounding Staple - Stainless steel • Base - PBT • Clamp - Stainless steel • Face - Nylon • Ground Contacts - .031" (.8) Brass • Mounting Screws - Stainless Steel • Mounting Strap - .040" (1) Galvanized steel • Power Contacts - .031 in. (.8) Brass • Terminal Screws - Brass

Mounting Type	Screw Mount
UPC	783585358581
Type	Weather Resistant Duplex
Material - Mounting Hardware	Screw Mounting
Item Type	Traditional Duplex
Material	Thermoplastic/Composite

Logistics

Carton Quantity	10
-----------------	----

Operational

Temperature Rating	• Maximum continuous 75°C
--------------------	---

Operating Temperature	• minimum -40°C (w/o impact) Maximum continuous 75°C and minimum -40°C without Impact
Horsepower - Maximum	0.5

Product Assets

- Catalog [English]
- Catalog Page [English]
- Installation Manual [French, English]



A Hubbell brand