

Industrial Grade, Pendant Controls, Two Button Compact Version, Single Speed Normally Open, Pilot Duty, 240VAC, Terminal Screws

By Hubbell Wiring Device-Kellems
Catalog # [CPB21](#)

Switches and Lighting Controls, Industrial Grade, Pendant Controls, Two Button Compact Version, Single Speed Normally Open, Pilot Duty, 240VAC, Terminal Screws, Yellow

Features

- Single-speed with mechanical interlock between pushbuttons.

Performance

Environmental - , Operating Temperatures - Max Continuous- 75 ° C, Minimum -40° w/o Impact

Specifications

Environmental Conditions	Indoor and Outdoor
EU RoHS Indicator	No
Nema Rating	NEMA 4X
Industry Standard(s)	UL Listed

Configuration

Contact Configuration	Momentary
-----------------------	-----------

Current

Amperage Rating	120V AC- 6A, 240V AC 35% PF- 3A, 125V DC- 1.1A, Inductive 250V- .55 A
Connectivity	Terminal Screws
Phase	Single Phase
Contact Rating	Pilot Duty Only

Dimensions

Length	9.13 in
Display Size	Compact



Weight	0.75 lb.
Height	2.38 in
Width	1.06 in
Dimensions	9.13 in x 1.06 in x 2.38 in

General

Color	Yellow
Style	Two Button
Ingress Protection	IP55
Enclosure Type	NEMA 4X
Series	Compact
UPC	783585106854
Type	Single Speed
Material - Mounting Hardware	Cable Mounted

Logistics

Pallet Quantity	1500
Carton Quantity	25

Operational

Actuator	Push Buttons
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Indicator(s) Type	None

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)