

1/2 Controlled EdgeConnect™ Series, 20A
Decorator Gray Duplex Receptacle

By Hubbell Wiring Device-Kellems
Catalog # [DR20STC1GY](#)

1/2 Controlled EdgeConnect™ 20A Decorator Gray Duplex Receptacle



Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Simple color coded plungers for easy and quick wiring
- Use small screwdriver to lift plunger and rewire as needed

Application

Spring clamp terminal strengthens over time providing a more reliable connection.

Specifications

Nema Rating	5-20R
Industry Standard(s)	• UL Listed to UL498 File No. E2186 • Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire

Current

Voltage Rating	125 V
Dielectric Strength	Withstands 2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Current Rating	20 A

Dimensions

Weight	0.2 lb.
--------	---------

Size	3.28x1.58x1.38 in
------	-------------------

General

Specifications	• Product Identification - Ratings are a permanent part of the device • Terminal Accomodation - #14 - #10AWG Wire (Solid or Stranded) Copper or UL listed CCA conductors only • Terminal Identification - Terminals Identified in Accordance with UL 498 and CSA
Color	Gray
Style	Decorator
UPC	783585757308
Type	Controlled
Item Type	Receptacle
Material	Thermoplastic/C
U_Flammability	UL 94 V-2
Series	EdgeConnect™ Series

Logistics

Pallet Quantity	4000
Carton Quantity	10

Operational

Operating Temperature	• Maximum continuous 75 °C • Minimum (w/o impact) -40 °C
-----------------------	--

Product Assets

[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)