

EdgeConnect™ Series, Decorator
Receptacle, Commerical Grade, Weather
Resistant, 2-Pole 3-Wire, 15A 125V, 5-15R,
Screwless Terminal, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [DR20STIWR](#)

Straight Blade Devices, EdgeConnect™ , Decorator Receptacle,
Commercial Grade, Weather Resistant, 2-Pole 3-Wire, 15A 125V, 5-15R,
Screwless Terminal, Ivory

Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Triple and Double Wipe Contacts
- Easy access split circuit tab

Specifications

Nema Rating	5-20R
Industry Standard(s)	• UL Listed to UL498 File No. E2186 • Certified to CSA 22.2 • No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant • UL 94 V-2

Conductor

Number Of Poles	2-Pole
Number Of Wires	3-Wire
Wire Size	#14 (Solid and Stranded) - #10 (Stranded) Copper Wire Only

Current

Interrupt Rating	Certified for current interrupting at full rated current A
Voltage Rating	125 V
Dielectric Strength	Withstands 2,000V minimum
Current / Amperage Rating	20 A

Dimensions

Weight	0.3 lb.
Size	3.28x1.58x1.38

General

Color	Ivory
Style	Style Line Decorator
Listings	Terminals Identified in Accordance with UL 498 and CSA 783585730219
UPC	783585730219
Type	Weather Resistant
Item Type	Receptacle
Material	Thermoplastic/C
Series	EdgeConnect™ Series

Logistics

Pallet Quantity	3300
Carton Quantity	10

Operational

Temperature Rating	• Maximum continuous 75°C • minimum -40°C (w/o impact)
--------------------	--

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)

