

EdgeConnect™ Series, Decorator  
Receptacle, Commerical Grade, Weather  
Resistant, Tamper Resistant, 2-Pole 3-Wire,  
15A 125V, 5-15R, Screwless Terminal, Orange

By Hubbell Wiring Device-Kellems  
Catalog # [DR20STOWRTR](#)

Straight Blade Devices, EdgeConnect™ , Decorator Receptacle,  
Commercial Grade, Weather Resistant, Tamper Resistant, 2-Pole 3-Wire,  
15A 125V, 5-15R, Screwless Terminal, Orange

Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Triple and Double Wipe Contacts
- Easy access split circuit tab

Specifications

|                      |                                                                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nema Rating          | 5-20R                                                                                                                                                                                                       |
| Industry Standard(s) | <ul style="list-style-type: none"><li>• UL Listed to UL498 File No. E2186</li><li>• Certified to CSA 22.2</li><li>• No. 42 File 285, Fed. Spec. W-C-596, NEMA® WD-6 Compliant</li><li>• UL 94 V-2</li></ul> |

Conductor

|                 |                                                            |
|-----------------|------------------------------------------------------------|
| Number Of Poles | 2-Pole                                                     |
| Number Of Wires | 3-Wire                                                     |
| Wire Size       | #14 (Solid and Stranded) - #10 (Stranded) Copper Wire Only |

Current

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Interrupt Rating          | Certified for current interrupting at full rated current A |
| Voltage Rating            | 125 V                                                      |
| Dielectric Strength       | Withstands 2,000V minimum                                  |
| Current / Amperage Rating | 20 A                                                       |



Dimensions

|        |                |
|--------|----------------|
| Weight | 0.3 lb.        |
| Size   | 3.28x1.58x1.38 |

General

|          |                                                                     |
|----------|---------------------------------------------------------------------|
| Color    | Orange                                                              |
| Style    | Style Line Decorator                                                |
| Listings | Terminals Identified in Accordance with UL 498 and CSA 783585730332 |
| UPC      | 783585730332                                                        |
| Type     | Weather Resistant & Tamper-Resistant Receptacle                     |
| Material | Thermoplastic/C                                                     |
| Series   | EdgeConnect™ Series                                                 |

Logistics

|                 |      |
|-----------------|------|
| Pallet Quantity | 3300 |
| Carton Quantity | 10   |

Operational

|                    |                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------|
| Temperature Rating | <ul style="list-style-type: none"><li>• Maximum continuous 75°C</li><li>• minimum -40°C (w/o impact)</li></ul> |
|--------------------|----------------------------------------------------------------------------------------------------------------|

Product Assets

[Catalog \[English\]](#)  
[Catalog Page \[English\]](#)  
[Installation Manual \[Spanish, French, English\]](#)