

Circuit Guard® Extra Heavy Duty Hard Wired
GFCI with Automatic Set, 30A, 240V AC,
Yellow

By Hubbell Wiring Device-Kellems
Catalog # [GFHW23105](#)

Power Protection Products, Hard Wired GFCI, Industrial/Commercial, No
Output, 30A 240V AC, 4-6 mA Trip Level, Yellow

Features

- Electromagnetic Latching Mechanism
- Trips if ground and neutral touch at load side
- Red blinking light plus optional audible alarm
- Open neutral protection Trips upon loss of neutral

Application

Wire Into Circuit

Performance

Electrical - Dielectric Withstand - 1500 VRMS across contact, 4000
VRMS between conductors & enclosure, Electrical - Operating Voltage
Range - 85% to 110%, Electrical - Rated Voltage - 120V AC, 240V AC &
120/240V, 3Ø 250V AC, 3Ø 120/208V AC, Electrical - Surge Withstand -
6000V impulse, 0.5 ms rise time 100kHz ringing frequency,
Environmental - Construction - Industrial grade design, Environmental -
Housing Rating - UL Type 4X, Environmental - Leakage Current - At 93%
Humidity leakage current is zero, Environmental - Operating Temperature
- -35°C to 66°C, -30°F to 150°F., Environmental - Type - Class A GFCI

Specifications

Industry Standard(s) UL Listed

Conductor

Conductor Size #10 AWG
Strands Multi
Number Of Conductors 3
Conductor Type Copper

Current

Amperage Rating 30 A
Voltage Rating Description 240 VAC
Current Rating 30 A
Voltage Rating 240 VAC
Connectivity Hard Wired



Current / Amperage Rating 30 A

Dimensions

Weight 1.6 lb.

General

Color Yellow
Style Automatic Set
Series Extra Heavy Duty
OEM Brand Name Hubbell Wiring Device-Kellems
Specifications

- Response Time - .025 sec. Max
- Switch Interface - Double Insulated
- Trip Level - 4 to 6 mA
- Unit Color - Gray with black cover
- Weight - 1.40 lbs.
- Wire Leads - #10 AWG, 24" long

UPC 783585005249
Type Hard Wired
Construction Fabricated
Item Type Industrial Grade
Material - Insulation Thermoplastic

Logistics

Carton Quantity 5

Operational

Temperature Rating -35 Degrees C to 66 Degrees C
 (-30 Degrees F to 150 Degrees F)

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)