

Circuit Guard® Extra Heavy Duty Portable
Straight Blade GFCI with Automatic Set, 30A,
3Ø 250V AC, 6', Yellow

By Hubbell Wiring Device-Kellems
Catalog # [GFP5315](#)

Power Protection Products, GFCI High Amperage Portables,
Industrial/Commercial, Auto Set, 30A 3-Phase 250V AC, 6' Cord Length,
4-6 mA Trip Level, Yellow

Features

- Electromagnetic Latching Mechanism
- Trips if ground and neutral touch at load side
- Red blinking light plus optional audible alarm
- Open neutral protection Trips upon loss of neutral

Application

Line Cord Only No Devices

Performance

Electrical - Dielectric Withstand - 1500 VRMS across contact, 4000 VRMS between conductors & enclosure, Electrical - Operating Voltage Range - 85% to 110%, Electrical - Rated Voltage - 120V AC, 240V AC, 120/240V AC, 3Ø 250V AC, 3Ø 120/208V AC, Electrical - Surge Withstand - 6000V impulse, 0.5 ms rise time 100kHz ringing frequency, Environmental - Construction - Industrial grade design, Environmental - Housing Rating - UL Type 4X, Environmental - Leakage Current - At 93% Humidity leakage current is zero, Environmental - Operating Temperature - -35°C to 66°C, -30°F to 150°F., Environmental - Type - Meets UL943 Class A GFCI

Specifications

Industry Standard(s) cCSA

Conductor

Conductor Size #10 AWG
Strands Multi
Number Of Conductors 4
Conductor Type Copper

Current

Amperage Rating 30 A
Voltage Rating Description 3 Phase 250 VAC
Current Rating 30 A
Voltage Rating 3 Phase 250 VAC
Connectivity Plug-In
Current / Amperage Rating 30 A



Dimensions

Outside Diameter 0.335
Weight 4.5 lb.

General

Color Yellow
Style Automatic Set
Series Extra Heavy Duty
OEM Brand Name Hubbell Wiring Device-Kellems
Specifications

- Cord Type - 2-50', 10/3 SJGOOW. 100', 8/3 SEOW
- Label Color - Yellow background with black lettering
- Response Time - .025 sec. Max
- Switch Interface - Double Insulated
- Trip Level - 4 to 6 mA
- Unit Color - Gray with black cover

UPC 783585521312
Type Portable, Straight Blade
Construction Fabricated
Item Type Industrial Grade
Material - Jacket PVC
Material - Insulation Elastomer

Logistics

Carton Quantity 5

Operational

Temperature Rating -35 Degrees C to 66 Degrees C
(-30 Degrees F to 150 Degrees F)

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)