

Extra Heavy Duty Industrial Tamper-Resistant/Weather Resistant AUTOGUARD® Self-Test GFCI Receptacle, 15A, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [GFSG5262YEL](#)

AUTOGUARD® Self-Test Tamper-Resistant Weather-Resistant GFCI Receptacle

Features

- CLAD® Protection: Filters out harmonics and transient noise for precise ground fault detection.
- AutoGuard® Self-Test: Automatically tests GFCI function every 30 seconds for ongoing safety.
- Tamper-Resistant Shutters: Patented mechanism protects against foreign object insertion.
- Triple Wipe Construction for enhanced blade contact and long lasting plug retention
- Hubbell Quality: Engineered for long-term durability in industrial settings.

Application

Kitchens, Bathrooms, Outdoors

Specifications

Environmental Conditions	Indoor Dry unless protected by additional means
Nema Rating	5-15R
Industry Standard(s)	Meets All NEC® Requirements

Conductor

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG
Number Of Poles	2-Pole

Current

Amperage Rating	15 A
Dielectric Strength	Withstands 1,500V minimum
Voltage Rating	125 V
Phase	Single Phase

Dimensions



Size 4.06x1.75x1.48

General

Color	Brown
Style	Standard
Sub Brand	AUTOGUARD®
Specifications	• Base - Nylon • Face - Nylon/PBT • Ground Contacts - Nickel Plated Brass • Mounting Screws - Stainless Steel • Mounting Strap -Nickel Plated Brass • Power Contacts - Nickel Plated Brass
Mounting Type	Screw Mount
UPC	783585751900
Type	Tamper-Resistant, Weather Resistant
Insulation Material	UL Standards Thermoplastic/Composite

Logistics

Pallet Quantity	1080
Carton Quantity	10

Operational

Temperature Rating	-35°C to 66°C or -30°F to 150°F
--------------------	---------------------------------

Product Assets

[Installation Manual \[Spanish, French, English\]](#)