

Commercial Grade, Panel Mount and
Specialty Switches, Bat Handle Switches,
Single Pole Single Throw 10A 240V /15A
125V, Wire Leads,

By Hubbell Wiring Device-Kellems
Catalog # [HBL118](#)

Switches and Lighting Controls, Commercial Grade, Panel Mount
and Specialty Switches, Bat Handle Switches, Single Pole Single
Throw 10A 240V /15A 125V, Wire Leads,

Features

- Nickel Plated for Corrosion Resistance

Performance

Environmental - Operating Temperatures - Max Continuous- 75
°C, Minimum -40 °C Without Impact

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Number Of Poles	Single Pole
-----------------	-------------

Configuration

Mounting Method	Panel Mount
-----------------	-------------

Current

Amperage Rating	10/15 A
Voltage Rating	240/120 VAC
Connectivity	Screw Terminals
Current / Amperage Rating	10/15 A

Dimensions

Length	1.78 in
Weight	0.05 lb.
Height	0.56 in
Width	0.67 in
Dimensions	1.78 in x 0.67 in x 0.56 in



General

Color	Metallic
Style	Screw Terminal
Series	Single Pole/Single Throw
Specifications	- Body Material - Impact Resistant Thermoplastic Body - Bushing - Brass- Nickel Plated - Contacts - Fine Silver - Strap Material - Nickel Plated - Toggle - Brass- Nickel Plated
UPC	783585016733
Type	General Purpose
Item Type	Panel Mount and Bat Handle Switch

Logistics

Carton Quantity	10
-----------------	----

Operational

Action	SPST
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)