

Hospital Call Switch, Toggle Switches,
General Purpose AC, Single Pole,
20A120/277V AC, Back and Side Wired,
With Lanyard

By Hubbell Wiring Device-Kellems
Catalog # [HBL1221GHCS](#)

Switches and Lighting Controls, Hospital Call Switch, Toggle
Switches, General Purpose AC, Single Pole, 20A120/277V AC,
Back and Side Wired, Gray, With Lanyard

Features

- Large brass binding head screws with deep slots
- Provides a means of alerting trouble
- Strip gauge for accurate wiring

Application

Back and Side Wired

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum
for 1 minute, Electrical - Max. Continuous Current - 20A, Electrical
- Max. Working Voltage - 277V AC, Electrical - Overload -
Minimum 4.8 times rated current for 100 cycles, Electrical -
Temperature Rise - 30°C maximum at rated current,
Environmental - Flammability - UL 94V-2, Environmental -
Operating Temperature - Max. continuous: 75°C,Min. continuous:
-40°C without impact, Mechanical - Terminal Accommodations -
#14 AWG min. - #10 AWG max. solid and stranded copper wire
only

Specifications

Industry Standard(s)	UL Listed
EU RoHS Indicator	No

Conductor

Number Of Poles	Single Pole
Wire Size	#14 AWG to #10 AWG

Current

Amperage Rating	20 A
Voltage Rating	120-277 VAC
Temperature Rise - Max.	30°C maximum at rated current
Voltage Rating Description	120-277 VAC
Connectivity	Back and Side Wired
Dielectric Strength	Withstands 1500V AC minimum for 1 minute



Current / Amperage Rating	20 A
Current Rating	20 A

Dimensions

Height	1.82 in
Width	1.45 in
Length	4.18 in
Dimensions	4.18 in x 1.45 in x 1.82 in

General

Specifications	• Base Material - Thermoset, Red • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Terminal Screws - Brass • Toggle Material - Nylon • Top Material - Thermoset, Gray
Color	Gray
Style	Single Pole
UPC	783585188010
Type	Toggle
Series	Heavy Duty

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	---

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[English\]](#)