

Switches and Lighting Controls, Illuminated
Industrial Grade, PresSwitch, General
Purpose AC, Four Way, 15A 120/277V AC,
Screw Terminals, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [HBL1259I](#)

Switches and Lighting Controls, Illuminated Industrial Grade,
PresSwitch, General Purpose AC, Four Way, 15A 120/277V AC,
Screw Terminals , Ivory

Features

- Large brass binding head screws with deep slots
- Thread cleaning captive mounting screw
- Strip gauge for accurate wiring

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum
for 1 minute, Electrical - Max. Continuous Current - 20A, Electrical
- Max. Working Voltage - 277V AC, Electrical - Overload -
Minimum 4.8 times rated current for 100 cycles, Electrical -
Temperature Rise - 30°C maximum at rated current,
Environmental - Flammability - UL 94V-2, Environmental -
Operating Temperature - Max. continuous: 75°C, Min. continuous:
-40°C without impact, Mechanical - Terminal Accommodations -
#14 AWG min. - #10 AWG max. solid and stranded copper wire
only

Specifications

EU RoHS Indicator	Yes
Industry Standard(s)	Fed. Spec. W-S-896

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Single Pole

Current

Amperage Rating	15 A
Voltage Rating Description	120 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	120 VAC
Temperature Rise - Max.	30°C maximum at rated current
Connectivity	Side Wired Only
Current / Amperage Rating	15 A

Dimensions

Length	3.28 in
Height	1.45 in
Width	1.5 in
Dimensions	3.28 in x 1.5 in x 1.45 in

General

Color	Ivory
Style	Four Way
Series	Illuminated
Specifications	• Top Material - Thermoplastic, Gray • Base Material - Thermoplastic, Black • Toggle Material - Nylon • Contacts - Silver Alloy • Terminal Screws - Brass • Auto Grounding Mounting Bridge - Zinc Plated Steel • Ground Screw - Brass (Green)
UPC	783585016801
Item Type	Four Way Toggle Switch

Logistics

Carton Quantity	10
-----------------	----

Operational

Indicator	Light On with Load Off
Action	DPDT
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Catalog Page \[English\]](#)

