

Switches and Lighting Controls, Industrial Grade, Toggle Switches, General Purpose AC, Three Way, 15A 347V AC, Terminal Screws, Black Nylon Key Guide

By Hubbell Wiring Device-Kellems
Catalog # [HBL18203LCN](#)

Switches and Lighting Controls, Industrial Grade, Toggle Switches, General Purpose AC, Three Way, 15A 347V AC, Terminal Screws, Black Nylon Key Guide

Features

- Large brass binding head screws with deep slots
- Lock circuits On or Off
- Strip gauge for accurate wiring

Application

General Purpose

Performance

Electrical - Dielectric Voltage - Withstands 1500V AC minimum for 1 minute, Electrical - Max. Continuous Current - 15A, Electrical - Max. Working Voltage - 277V AC, Electrical - Overload - Minimum 4.8 times rated current for 100 cycles, Electrical - Temperature Rise - 30°C maximum at rated current, Environmental - Flammability - UL 94V-2, Environmental - Operating Temperature - Max. continuous: 75°C, Min. continuous: -40°C without impact, Mechanical - Terminal Accommodations - #14 AWG min. - #10 AWG max. solid and stranded copper wire only

Specifications

EU RoHS Indicator	No
Industry Standard(s)	UL Listed

Conductor

Wire Size	#14 AWG to #10 AWG
Number Of Poles	Single Pole

Configuration

Contact Configuration	3-Position
-----------------------	------------

Current

Amperage Rating	15 A
Voltage Rating Description	347 VAC
Dielectric Strength	Withstands 1500V AC minimum for 1 minute
Current Rating	15 A
Voltage Rating	347 VAC
Temperature Rise - Max.	30°C maximum at rated current
Wattage	6940 W
Connectivity	Back and Side Wired



Current / Amperage Rating	15 A
Contact Rating	Full Rated

Dimensions

Length	4.06 in
Display Size	Standard Product Size
Weight	0.2 lb.
Height	1.86 in
Width	1.3 in
Dimensions	4.06 in x 1.3 in x 1.86 in

Force Related

Load Capacity	Inductive or Resistive
---------------	------------------------

General

Color	Black
Style	Three Way
Series	Extra Heavy Duty
Lock Type	Non-Cylindrical
Specifications	• Base Material - Thermoset, Color Coded by Amperage • Contacts - Silver Alloy • Ground Screw - Brass (Green) • Key Guide - Metallic, Black • Terminal Screws - Brass • Top Material - Thermoset
UPC	783585924748
Type	Locking
Material - Mounting Hardware	Mounting Screws

Logistics

Carton Quantity	10
-----------------	----

Operational

Actuator	Double Ended Key
Action	Snap
Temperature Rating	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Indicator(s) Type	Dot Indicates On

Product Assets

[Catalog \[English\]](#)

[Catalog Page \[English\]](#)



A Hubbell brand