

HUBBELL
Wiring Device-Kellems

**Locking Devices, Hubbellock, Industrial,
Flanged Inlet, 30A 600V AC, 20A 250V
DC, Non-NEMA, Screw Terminal, FS/FD
Box Mounting**

By Hubbell Wiring Device-Kellems
Catalog # [HBL20418](#)

Locking Devices, Hubbellock, Industrial, Flanged Inlet, 30A 600V
AC, 20A 250V DC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw
Terminal, FS/FD Box Mounting



Features

- Molded-in male contacts are resistant to damage and provide a consistently positive connection
- Insulated non-metallic housing enhances safety and abuse resistance
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Metallic weather protective spring loaded cover provides protection from moisture and dust

Application

Extra Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage - 2,000V minimum, Environmental - Flammability - UL 94 V0 for Receptacles and Inlets.HB or better for Plugs and Connectors, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #10 AWG - #6 AWG solid or stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications


Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA Standard • Listed to UL Standard

Conductor

Number Of Wires	4-Wire
Wire Size	#10 AWG to #6 AWG
Number Of Poles	3-Pole

Current

Amperage Rating	30 A
Voltage Rating Description	250 VDC/600 VAC



Dielectric Strength	Withstands 2,000V minimum
Current Rating	20 A
Voltage Rating	250 VDC/600 VAC
Connectivity	Back Wired Screw Terminals
Current / Amperage Rating	30 A

Dimensions

Length	4.56 in
Display Size	Standard Sized Product
Weight	0.85 lb.
Height	2.4 in
Width	2.84 in
Dimensions	4.56 in x 2.84 in x 2.4 in

General

Color	Metallic
Specifications	• Contacts - Brass • Housing - Cast Aluminum • Inlet Interior - Thermoset • Terminal Screws - Zinc plated steel
UPC	783585017457
Type	Flanged Inlet
Material - Mounting Hardware	Screw Mounting
Insulation	Insulated Body
Item Type	20A/30A Grounding Hubbellock® Flanged Inlet
Material	Aluminum, Cast

Logistics

Carton Quantity	10
-----------------	----

Operational

Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
-----------------------	--

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[French, English\]](#)