

Locking Devices, Hubbellock, Industrial,
Female Connector Body, 20A 125V, 2-Pole
3-Wire Grounding, Non-NEMA, Screw
Terminal, Black and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL23032B](#)

Hubbellock Industrial Female Connector Body 20A

Features

- Spring loaded safety shutter contains arcing when mating or un-mating devices under load
- Spring loaded safety shutter automatically ejects the plug eliminating contact teasing
- Box terminals in conjunction with screws with pressure pads provide maximum termination strength and dependability
- Three-piece clamp assembly provides maximum strain relief and protects against entry of moisture and dust

Application

Heavy Duty Industrial

Performance

Electrical - Current Interrupting - Certified for current interrupting at full rated current, Electrical - Dielectric Voltage Withstand - 2,000V minimum, Environmental - Flammability - HB or better, Environmental - Moisture Resistance - IP30 Suitability, Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact), Mechanical - Terminal Accommodation - #16 AWG - #12 AWG stranded copper wire only., Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	No
Industry Standard(s)	• Certified to CSA C22.2 No.42 • Listed to UL 498

Conductor

Number Of Wires	3-Wire
Wire Size	#16 AWG to #12 AWG
Number Of Poles	2-Pole
Cable Range	0.320 - 0.660 in

Current

Amperage Rating	20 A
-----------------	------



Voltage Rating Description	125 V
Current Rating	20 A
Voltage Rating	125 V
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	20 A

Dimensions

Length	1.63 in
Display Size	Standard
Weight	0.35 lb.
Height	3.56 in
Width	1.72 in
Dimensions	1.63 in x 1.72 in x 3.56 in

General

Color	Black
Specifications	• Assembly Screws - Stainless Steel • Contact Housing - Thermoset • Contacts - Bronze • Cord Clamp Material - Nylon • Device Color - Black/White • Housing - Nylon • Shutter - Thermoset
UPC	783585017556
Type	Connector Body
Material - Mounting Hardware	Cord Mounted
Insulation	Insulated Body
Item Type	20A Grounding Hubbellock® Female Connector
Material	Composite

Logistics

Carton Quantity	20
-----------------	----

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[Spanish, French, English\]](#)